

# Safety Data Sheet

DryLube

## SECTION I - IDENTIFICATION

**PRODUCT IDENTIFIER:** DryLube  
**PRODUCT CODE:** 56600023-16AR  
**RECOMMENDED USE:** Dry Lubricant  
**RESTRICTIONS ON USE:** None known.  
**COMPANY NAME:** Brodi Specialty Products  
**COMPANY ADDRESS:** 3175 14th Avenue Unit 1, Markham, ON L3R 0H1  
**COMPANY PHONE:** 1-877-744-0751  
**EMERGENCY PHONE:** 800-255-3924

## SECTION II – HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable Aerosol: Category 1  
Gases Under Pressure: Liquefied Gas  
Skin Irritant: Category 2  
Eye Irritant: Category 2A  
Specific Target Organ Toxicity (Single Exposure): Category 3  
Aspiration Hazard: Category 1

**HAZARD STATEMENT(S): DANGER:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: N/A

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

## SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Heptane	142-82-5	30-40%
Isopropyl Alcohol	67-63-0	15-25%
Propane	74-98-6	15-25%
N-Butane	106-97-8	15-25%
Naphtha (petroleum), light alkylate	64741-66-8	1-5%

## SECTION IV - FIRST AID MEASURES

**EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**INGESTION:** If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

**INHALATION:** Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

## Safety Data Sheet

### DryLube

**SKIN:** If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk

**CHRONIC HEALTH HAZARDS:** Repeated or prolonged exposure may be toxic to kidneys, liver, skin, central nervous system (CNS).

**NOTE TO PHYSICIAN:** If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

## SECTION V – FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Dry chemical, foam, or carbon dioxide (CO<sub>2</sub>).

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers. Shut off all sources of ignition.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. May develop a flammable atmosphere in confined areas.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon, low molecular weight hydrocarbons.

## SECTION VI – ACCIDENTAL RELEASE MEASURES

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Clean up with non-combustible material like vermiculite, sand or earth. If many cans are opened remove ignition sources.

Prevent spill from entering sewers, storm drains, and natural waterways.

**WASTE DISPOSAL:** Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers.

**RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

## SECTION VII – HANDLING AND STORAGE

**HANDLING AND STORAGE:** Use only with adequate ventilation. Wear appropriate protective equipment. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Store in cool, dry, ventilated area. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**OTHER PRECAUTIONS:** Keep out of the reach of children.

**INCOMPATIBILITY:** Avoid heat, flame, and contact with strong oxidizing agents.

## SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Heptane	500 ppm	400 ppm
Isopropyl Alcohol	400 ppm	200 ppm
Propane	1000 ppm	1000 ppm
N-Butane	Not Established	1000 ppm
Naphtha (petroleum), light alkylate	Not Established	Not Established

**ENGINEERING CONTROLS / VENTILATION:** Use only outdoors or in a well-ventilated area.

**RESPIRATORY PROTECTION:** Use only in well ventilated areas. If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses and chemical resistant gloves.

**ADDITIONAL MEASURES:** Wash hands thoroughly after handling.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** White Hazy Spray

**ODOR:** Petroleum odor

**ODOR THRESHOLD:** N/D

**pH:** N/A

## Safety Data Sheet

### DryLube

**MELTING POINT/FREEZING POINT:** N/D  
**INITIAL BOILING POINT AND BOILING RANGE:** N/D  
**FLASH POINT:** N/D  
**EVAPORATION RATE:** N/D  
**FLAMMABILITY(solid/gas):** Extremely Flammable Aerosol  
**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**  
    **LOWER FLAMMABILITY LIMIT:** N/D  
    **UPPER FLAMMABILITY LIMIT:** N/D  
    **EXPLOSIVE LIMIT LOWER (%):** N/D  
    **EXPLOSIVE LIMIT UPPER (%):** N/D  
**VAPOR PRESSURE (mm Hg):** N/D  
**VAPOR DENSITY (AIR=1):** N/D  
**RELATIVE DENSITY (H<sub>2</sub>O=1):** 0.71 - 0.76  
**SOLUBILITY(IES):** Non-soluble in water.  
**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D  
**AUTOIGNITION TEMPERATURE:** N/D  
**DECOMPOSITION TEMPERATURE:** N/D  
**VISCOSITY:** N/D

## SECTION X – STABILITY AND REACTIVITY

**REACTIVITY:** None known.  
**CHEMICAL STABILITY:** Stable.  
**POSSIBLE HAZARDOUS REACTIONS:** None known  
**CONDITIONS TO AVOID:** Temperatures greater than 122 °F and sources of ignition.  
**INCOMPATIBLE MATERIALS:** Avoid heat, flame, and contact with strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon.

## SECTION XI – TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** **Heptane** (142-82-5) LC<sub>50</sub> (Vapors, Mice) 1600 ppm **Isopropyl Alcohol** (67-63-0) Oral LD<sub>50</sub> (Rat): 5045mg/kg; Dermal LD<sub>50</sub> (Rabbit): 12870mg/kg; Inhalation LC<sub>50</sub> (Rat, 4h): 78.6 mg/L  
**ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin  
**EYES:** Causes irritation, redness, tearing, pain, blurred vision.  
**INGESTION:** May cause gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, dizziness, drowsiness, signs of intoxication, incoordination, and slurred speech depending on the amount ingested. Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia or edema.  
**INHALATION:** May cause irritation to the respiratory tract, dizziness, headaches, drowsiness, unconsciousness and other central nervous system effects including death with excessive or prolonged exposure.  
**SKIN:** Brief contact is not irritating. May cause irritation, dryness, redness, localized defatting with prolonged or repeated contact. Removes natural oils and fats from skin.  
**MEDICAL CONDITION AGGRAVATED:** Asthma, bronchitis, emphysema and other lung diseases and chronic nose, sinus or throat conditions. Skin irritation may be aggravated in individuals with existing skin disorders.  
**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision  
Skin: defatting and dermatitis  
Inhalation: Anesthetic, irritation, Central Nervous System depression  
Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk  
**CHRONIC HEALTH HAZARDS:** Repeated or prolonged exposure may be toxic to kidneys, liver, skin, central nervous system (CNS).  
**CARCINOGENICITY:** OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

## SECTION XII – ECOLOGICAL INFORMATION

**ECOTOXICITY:** Avoid release to the environment. **Isopropyl Alcohol** (67-63-0) LC<sub>50</sub> (Fathead Minnow, 96 hrs) 9640 mg/L **n-Heptane** (142-82-5) EC<sub>50</sub> (Daphnia) 0.2 mg/L  
**PERSISTENCE AND DEGRADABILITY:** Component or components of this product are not biodegradable.  
**BIOACCUMULATIVE POTENTIAL:** This product is not expected to bioaccumulate.  
**MOBILITY IN SOIL:** This product is mobile in soil.  
**OTHER ADVERSE EFFECTS:** None known.

# Safety Data Sheet

DryLube

## SECTION XIII – DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers.

**RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

## SECTION XIV - TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKING GROUP:** N/A

### AIR SHIPMENT

**PROPER SHIPPING NAME:** Aerosols, flammable

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKING GROUP:** N/A

### SHIPPING BY WATER:

#### VESSEL (IMO/IMDG)

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKING GROUP:** N/A

**ENVIRONMENTAL HAZARDS WATER:** Marine Pollutant

## SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** All Chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** None

**SARA 311/312 HAZARD CATEGORIES:** Flammable (gases, aerosols, liquids, solids). Gas under pressure. Skin corrosion or irritation. Serious eye damage or eye irritation. Specific target organ toxicity (single or repeated exposure). Aspiration hazard.

**SARA 313 REPORTABLE INGREDIENTS:** None.

**STATE REGULATIONS:** California Proposition 65: None. Heptane (142-82-5) Director's List of Hazardous Substances: CA;

Toxic Substances Disclosure to Employees Act: IL; Right-to-Know: MA, MN, NJ, PA, RI. Isopropyl Alcohol (67-63-0)

Director's List of Hazardous Substances: CA; Toxic Substances Disclosure to Employees Act: IL; Right-to-Know: FL, NJ, PA, MN, MA, RI.

**INTERNATIONAL REGULATIONS:** Canadian Domestic Substance List (DSL): All ingredients are listed.

**VOLATILE ORGANIC COMPOUNDS (VOC):** 98.8%

**NFPA HEALTH:** 1

**HMIS HEALTH:** 1

**NFPA FLAMMABILITY:** 3

**HMIS FLAMMABILITY:** 3

**NFPA REACTIVITY:** 0

**HMIS REACTIVITY:** 0

**NFPA OTHER:** None

**HMIS PROTECTION:** B

## SECTION XVI - OTHER INFORMATION

**PREPARATION BY:** Roberto Cerón

**DATE PREPARED:** 01/06/2014

**REVISION DATE:** 06/21/2021

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained

## **Safety Data Sheet**

### **DryLube**

from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.