

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).  
Date of Issue: 11/14/2018 Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Epoxycoat Fast Dry

#### 1.2. Intended Use of the Product

No use is specified.

#### 1.3. Name, Address, and Telephone of the Responsible Party

Brodi Specialty Products Ltd.  
3175 14th Ave Unit 1  
Markham, Ontario L3R0H1  
905-475-6084

#### 1.4. Emergency Telephone Number

**Emergency Number** : 905-305-8551

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Aquatic Acute 2	H401
Aquatic Chronic 2	H411

Full text of hazard classes and H-statements : see Section 16.

#### 2.2. Label Elements

##### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



**Signal Word (GHS-US/CA)** :

Warning

**Hazard Statements (GHS-US/CA)** :

H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H401 - Toxic to aquatic life.  
H411 - Toxic to aquatic life with long lasting effects.

**Precautionary Statements (GHS-US/CA)** :

P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 - Specific treatment (see Section 4 on this SDS).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P391 - Collect spillage.

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P501 - Dispose of contents/container in accordance with local, regional, national, provincial, territorial and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Bisphenol A diglycidyl ether	2,2-Bis(p-glycidyloxyphenyl)propane / Diglycidyl bisphenol A ether / Diglycidyl ether of bisphenol A / 4,4'-Isopropylidenediphenol diglycidyl ether / 2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane / Propane, 2,2-bis(p-(2,3-epoxypropoxy)phenyl)- / Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis- / BADGE / 2,2-Bis(4-hydroxyphenyl)propane bis(2,3-epoxypropyl) ether / DGEBA / 2,2-Bis[4-(2,3-epoxypropoxy)phenyl]propane / Bis[4-(2,3-epoxypropoxy)phenyl]propane / Bis-[4-(2,3-epoxipropoxy)phenyl]propane / Bis[4-(2,3-epoxipropoxy)phenyl]propane / Bisoxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]- / 2,2'-[(1-Bethylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane / 2,2-Bis[4-(oxiran-2-ylmethoxy)phenyl]propane	(CAS-No.) 1675-54-3	70	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Titanium dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO <sub>2</sub> ) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / TITANIUM DIOXIDE / Titanium oxide	(CAS-No.) 13463-67-7	25	Not classified
Carbon black	C.I. 77266 / C.I. Pigment Black 6 / C.I. Pigment Black 7 / Carbon blacks / Lampblack / CI 77266 / Vegetable carbon / Microjet Black CW / Pigment Black 7 / Coal soot / Coal soots / Channel black / Bonjet Black CW / Carbon Black	(CAS-No.) 1333-86-4	5	Comb. Dust

Full text of H-phrases: see Section 16.

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes serious eye irritation. Causes skin irritation. Skin sensitization.

**Inhalation:** Prolonged exposure may cause irritation.

**Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** None expected under normal conditions of use.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, dry chemical, foam, carbon dioxide.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Smoke. Phenolic compounds.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

#### Reference to Other Sections

Refer to Section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing.

##### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

##### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

#### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Possibility of dangerous reaction occurrence: curing with hardeners of Lewis acids/bases type may proceed very violently. Conditions to be avoided: avoid exposure to direct sunlight and humidity.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Avoid contact with skin, eyes and clothing.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Amines, amides that cause the substance curing, strong oxidizers and strong mineral acids or bases.

### 7.3. Specific End Use(s)

No use is specified.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in Section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2.4 mg/m <sup>3</sup> (CIB 63-fine) 0.3 mg/m <sup>3</sup> (CIB 63-ultrafine, including engineered nanoscale)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 3 mg/m <sup>3</sup> (respirable fraction)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nunavut	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Québec	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	30 mppcf 10 mg/m <sup>3</sup>

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Carbon black (1333-86-4)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> (Carbon black in presence of Polycyclic aromatic hydrocarbons)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	1750 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable particulate matter)
Nunavut	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable particulate matter)
Québec	VEMP (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Not available
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see Section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. **Incompatible Materials:** Amines, amides that cause the substance curing, strong oxidizers and strong mineral acids or bases.
- 10.6. **Hazardous Decomposition Products:** None expected under normal conditions of use.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** None expected under normal conditions of use.

### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Bisphenol A diglycidyl ether (1675-54-3)	
LD50 Oral Rat	11300 µl/kg
LD50 Dermal Rabbit	20000 mg/kg

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

ATE US/CA (dermal)	20,000.00 mg/kg body weight
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Carbon black (1333-86-4)	
LD50 Oral Rat	> 8000 mg/kg
Bisphenol A diglycidyl ether (1675-54-3)	
IARC Group	3
Titanium dioxide (13463-67-7)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Carbon black (1333-86-4)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Bisphenol A diglycidyl ether (1675-54-3)	
EC50 Daphnia 1	1.7 mg/l
Carbon black (1333-86-4)	
EC50 Daphnia 1	5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)

### 12.2. Persistence and Degradability

EP100 - Part A	
Persistence and Degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

EP100 - Part A	
Bioaccumulative Potential	Not established.

### 12.4. Mobility in Soil

Not available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, provincial, territorial and international regulations

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (EPOXY RESIN)
Hazard Class	: 9
Identification Number	: UN3082
Label Codes	: 9
Packing Group	: III
Marine Pollutant	: Marine pollutant
ERG Number	: 171



### 14.2. In Accordance with IMDG

# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet


According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Proper Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (EPOXY RESIN)  
**Hazard Class** : 9  
**Identification Number** : UN3082  
**Label Codes** : 9  
**Packing Group** : III  
**EmS-No. (Fire)** : F-A  
**EmS-No. (Spillage)** : S-F  
**Marine pollutant** : Marine pollutant




### 14.3. In Accordance with IATA

**Proper Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (EPOXY RESIN)  
**Hazard Class** : 9  
**Identification Number** : UN3082  
**Label Codes** : 9  
**Packing Group** : III  
**ERG Code (IATA)** : 9L



### 14.4. In Accordance with TDG

**Proper Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (EPOXY RESIN)  
**Hazard Class** : 9  
**Identification Number** : UN3082  
**Label Codes** : 9  
**Packing Group** : III  
**Marine Pollutant (TDG)** : Marine pollutant



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>EP100 - Part A</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Respiratory or skin sensitization
<b>Bisphenol A diglycidyl ether (1675-54-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Titanium dioxide (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Carbon black (1333-86-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. US State Regulations

#### California Proposition 65



**WARNING:** This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer.

For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Titanium dioxide (13463-67-7)	X			
Carbon black (1333-86-4)	X			
<b>Titanium dioxide (13463-67-7)</b>				
U.S. - Massachusetts - Right To Know List				
U.S. - New Jersey - Right to Know Hazardous Substance List				
U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Carbon black (1333-86-4)</b>				
U.S. - Massachusetts - Right To Know List				
U.S. - New Jersey - Right to Know Hazardous Substance List				



# Epoxycoat Fast Dry (Part - A)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

U.S. - Pennsylvania - RTK (Right to Know) List

### 15.3. Canadian Regulations

#### Bisphenol A diglycidyl ether (1675-54-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 11/14/2018

#### Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

#### GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)