

SAFETY DATA SHEET

1. Identification

Product identifier: GLOOB OPEN GEAR LUBRICANT

Other means of identification

SDS number: RE1000017063

Recommended restrictions

Product use: Lubricant

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: BRODI SPECIALTY PRODUCTS LTD
Address: 3175 14TH AV, UNIT 1
MARKHAM, ONTARIO L3R 0H1
Telephone: 877-744-0751
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Germ Cell Mutagenicity Category 2
Carcinogenicity Category 1A

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing genetic defects.
May cause cancer.

Precautionary Statements

- Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
- Response:** IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
- Storage:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Butane		106-97-8	30 - 60%
Asphalt		8052-42-4	10 - 30%
Trichloroethylene		79-01-6	10 - 30%
Propane		74-98-6	10 - 30%
Molybdenum sulfide (MoS ₂)		1317-33-5	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** No data available.
- Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

- Treatment:** No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Butane	STEL	1,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Butane	STEL	750 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
	TWA	600 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
Butane	TWA	800 ppm 1,900 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Butane	TWA	1,000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Butane	8 HR ACL	1,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Butane	STEL	1,000 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
	15 MIN ACL	1,250 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Butane	STEL	1,000 ppm	US. ACGIH Threshold Limit Values, as amended (03 2018)
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction. - as benzene soluble aerosol	8 HR ACL	0.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	15 MIN ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Asphalt - Inhalable fume. - as benzene solubles	TWA	0.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Asphalt - Inhalable fume. - as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2018)
Trichloroethylene	TWA	50 ppm 269 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Trichloroethylene	STEL	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Trichloroethylene	TWA	10 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2008)
Trichloroethylene	8 HR ACL	50 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Trichloroethylene	STEL	25 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	STEL	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2008)

Trichloroethylene	TWA	50 ppm 269 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	200 ppm 1,070 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	100 ppm 537 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
	15 MIN ACL	100 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	10 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Ethene, 1,1,2-trichloro-	TWA	10 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	25 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Propane	TWA	1,000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Propane	8 HR ACL	1,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Propane	TWA	1,000 ppm 1,800 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Propane	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	15 MIN ACL	1,250 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Molybdenum sulfide (MoS2) - Total - as Mo	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Molybdenum sulfide (MoS2) - Respirable. - as Mo	TWA	3 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Molybdenum sulfide (MoS2) - Inhalable	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Molybdenum sulfide (MoS2) - Respirable.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Molybdenum sulfide (MoS2) - Inhalable fraction. - as Mo	TWA	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Molybdenum sulfide (MoS2) - Respirable fraction. - as Mo	TWA	3 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Molybdenum sulfide (MoS2) - Respirable fraction. - as Mo	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Molybdenum sulfide (MoS2) - Inhalable fraction. - as Mo	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Molybdenum sulfide (MoS2) - Inhalable fraction. - as Mo	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Molybdenum sulfide (MoS2) - as Mo	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Molybdenum sulfide (MoS2) - Respirable fraction. - as Mo	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (2009)
Molybdenum sulfide (MoS2) - Inhalable fraction. - as Mo	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2009)
Oxirane, 2-(chloromethyl)-	TWA	0.5 ppm 1.9 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Oxirane, 2-(chloromethyl)-	8 HR ACL	0.5 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	1.5 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)

Oxirane, 2-(chloromethyl)-	TWA	0.5 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Oxirane, 2-(chloromethyl)-	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Oxirane, 2-(chloromethyl)-	TWA	0.1 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Oxirane, 2-(chloromethyl)-	TWA	2 ppm 7.6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Oxirane, 2-(chloromethyl)-	TWA	0.5 ppm	US. ACGIH Threshold Limit Values, as amended (2008)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	No data available.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	-104.44 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.

Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	3,792 - 5,171 hPa (20 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	Not classified for acute toxicity based on available data.
Specified substance(s):	
Asphalt	LD 50 (Rat): > 5,000 mg/kg

Trichloroethylene LD Lo (Rat): 5,620 mg/kg
LD 50: > 5,000 mg/kg

Molybdenum sulfide (MoS₂) LD 50: > 5,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Asphalt LD 50 (Rabbit): > 2,000 mg/kg

Trichloroethylene LD 50: > 2,000 mg/kg

Molybdenum sulfide (MoS₂) LD 50: > 5,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Butane LC 50: > 100 mg/l
LC 50: > 100 mg/l

Asphalt LC 50: > 20 mg/l
LC 50: > 5 mg/l
LC 50 (Rat): > 94.4 mg/m³

Trichloroethylene LC 50: > 20 mg/l
LC 50: > 20 mg/l

Propane LC 50: > 100 mg/l
LC 50: > 100 mg/l

Molybdenum sulfide (MoS₂) LC 50: > 100 mg/l
LC 50: > 100 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
Asphalt NOAEL (Rabbit(Female, Male), Dermal, 28 d): 2,000 mg/kg Dermal Experimental result, Key study
Trichloroethylene NOAEL (Rat(Male), Inhalation): 100 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Male), Oral, 52 Weeks): 50 mg/kg Oral Experimental result, Key study
Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Asphalt in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Asphalt Rabbit, 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Asphalt Skin sensitization:, in vivo (Guinea pig): Not sensitising

Carcinogenicity

Product: No data available.

Specified substance(s):

Trichloroethylene Potential cancer hazard.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Asphalt Overall evaluation: 2B. Possibly carcinogenic to humans.

Trichloroethylene Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Ethene, 1,1,2-trichloro- Year first listed as Known carcinogen: 2000. Hazard Designation: Known To Be Human Carcinogen.

ACGIH Carcinogen List:

Ethene, 1,1,2-trichloro- Group A2: Suspected human carcinogen.

Germ Cell Mutagenicity**In vitro**

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:****Fish**

Product: No data available.

Specified substance(s):

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Asphalt LL 50 (Oncorhynchus mykiss, 96 h): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Trichloroethylene LC 50 (Pimephales promelas, 96 h): 44.1 mg/l Experimental result, Supporting study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Asphalt LL 50 (Daphnia magna, 48 h): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Trichloroethylene IC 50 (Daphnia magna, 48 h): 20.8 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Asphalt LL 50 (Oncorhynchus mykiss): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Trichloroethylene NOAEL (Jordanella floridae): 5.76 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Asphalt NOAEL (Daphnia magna): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Trichloroethylene 19 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Trichloroethylene Lepomis macrochirus, Bioconcentration Factor (BCF): 17 Aquatic sediment
Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Butane	No data available.
Asphalt	No data available.
Trichloroethylene	No data available.
Propane	No data available.
Molybdenum sulfide (MoS ₂)	No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information**TDG**

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, Flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	—
EmS No.:	
Packing Group:	—
Environmental Hazards:	Yes
Marine Pollutant	No
Special precautions for user:	Not regulated.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, Flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	—
EmS No.:	
Packing Group:	—
Environmental Hazards:	Yes
Marine Pollutant	No
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, Flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	—
Packing Group:	—
Environmental Hazards:	Yes
Marine Pollutant	No
Special precautions for user:	Not regulated.
Cargo aircraft only:	Allowed.

15. Regulatory information

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Chemical Identity

Trichloroethylene

Oxirane, 2-(chloromethyl)-

Export Control List (CEPA 1999, Schedule 3)

Not Regulated

National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional Reporting Requirements

NPRI PT5

Butane

Propane

Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)

NPRI

Trichloroethylene

Greenhouse Gases

Not Regulated

Controlled Drugs and Substances Act

CA CDSI Not Regulated

CA CDSII Not Regulated

CA CDSIII Not Regulated

CA CDSIV Not Regulated

CA CDSV Not Regulated

CA CDSVII Not Regulated

CA CDSVIII Not Regulated

Precursor Control Regulations

Not Regulated

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	On or in compliance with the inventory
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	On or in compliance with the inventory
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date: 06/05/2020

Revision Date: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.